



HYPER T 2021



Equipped with:

- Four Pole Electric Motor with Thermal Protection and Water Cooling
- Three Ceramic Pistons
- Crankshaft Pump and Brass Pump Head with Built-In By-Pass Valve
- Integrated Elastic Joint
- Low Voltage and Delayed Total Stop
- Suction and Delivery Stainless Steel Valves
- Vertical Burner with High Thermal Efficiency
- Adjustable Temperature Thermostat
- Detergent Tank for Built In High Pressure Application
- **Stainless Steel Heating Coil with 3 Year Warranty**

Standard equipment:

- 00080-01694 - AL55 Pressure Adjustable Industrial Gun



- 00080-01727 Industrial Spray Lance



- 00080-02347 10M Double Steel Braided Hose



- 00080-03158 Nozzle



Optional:

- 0.999.0129 Turbo Head



- 0.999.0100 20M Dbl Steel Braided Hose
- 0.999.0130 30M Dbl Steel Braided Hose

(* Requires 00009-02101 Coupling)



* More Options Available

HYPER T 2021

Code	36074-00054
Standard Operating Pressure	3000 PSI
Maximum Water Volume	21 Litres/Minute, 1260 Litres/Hour
Motor Specifications	415V (20 Amp), 3Ph, 9.7KW (12.9HP)
Pump Type/RPM	CL5/1450
Max. Water Outlet Temperature	140 °C
Dimension/Weight	78x130x115cm/171 Kg