



## WALLMOUNT



### Standard equipment:

- 00080-01695 - AL55 Industrial Gun



- 00080-01727 Industrial Spray Lance



- 00080-02347 10M Double Steel Braided Hose



- 00080-03149 Nozzle



### Equipped with:


- Four Pole Electric Motor with Thermal Protection and Water Cooling (Water Cooling on 415v only)
- Three Ceramic Coated Pistons
- Brass Crankshaft Pump Head with Built-In By-Pass Valve
- Integrated Elastic Motor/Pump Coupling for Shock Absorption
- Low Voltage and Delayed Total Stop
- Suction and Delivery Stainless Steel Valves
- Glycerine Pressure Gauge
- Stainless Steel Cabinet and Chassis
- Zero Line/Hose Pressure Unloader System

### Optional:

- 6.602.0051 Industrial Foaming Lance  
(\* Requires 0.999.1015 Coupling)



- 0.999.0170 360 Degree Ceiling Boom  
(Differing Sizes Available)



- Hose reels, differing sizes and types.  
Ask for Options.



\* More Options Available

	WALLMOUNT 1211 (240v)	WALLMOUNT 2015 (415v)
Code	36077-00048	36077-00044
Standard Operating Pressure	1740 PSI	3000 PSI
Maximum Water Volume	11.6 Litres/Minute, 696 Litres/Hour	15 Litres/Minute, 900 Litres/Hour
Motor Specifications	240V (15 Amp), 1Ph, 3.0KW (4.0HP)	415V (20 Amp), 3Ph, 7.3KW (9.7HP)
Pump Type/RPM	CL5/1450	CL5/1450
Max. Water Outlet Temperature	40 °C	40 °C
Dimension/Weight	75x50x31cm/42 Kg	75x50x31cm/46 Kg